

POS Peripherals

Accessories

Essae[®]
...for Excellence



PR-65



PR-55



Model	PR-65	PR-55
Printing method	Direct Thermal	Direct Thermal
Printing speed	220 mm / sec (max)	200 mm / sec (max)
Paper width	79.5+ 0.5 mm	79.5+ 0.5 mm
Printer interface	Serial, USB & Ethernet	USB & Ethernet
Cutter	Full or Partial cut	Partial cut
Reliability	Printer head life : 100 km / Auto Cutter 1.5 Million cuts	Printer head life : 100 km / Auto Cutter 1 Million cuts
Power supply	DC 24 V / 2.5 A	DC 24 V / 1.5 A
Cash drawer interface	RJ-11 Connector	RJ-11 Connector
Software driver	Windows drivers, ESC/POS, OPOS Driver, JPOS Driver, CUPS Driver, Virtual COM USB Driver, SDK (Win, Android & iOS)	Windows drivers, ESC/POS, OPOS Driver, JPOS Driver, CUPS Driver, Virtual COM USB Driver, Android & iOS SDK.
Barcode printing support	QR code EAN-8, EAN-13, Code 39, Code 128, ITF UPC-A, UPC-E, Codabar	QR code EAN-8, EAN-13, Code 39, Code 128, ITF UPC-A, UPC-E, Codabar
Sensor	Cover open, Paper end	Paper end, Paper low, Cover open
Printer dimension (WxDxH) mm	142 x 185 x 136	145 x 123.5 x 121.6
Printer Weight	1.02 kg	1.35 kg

Reliability at its best!



Cash Drawer



Model	HS-410A
Interface	24 V DC/1 A, RJ-11 Connector
MOC	Body-Metal, Tray-ABS Plastic, Clip-Metal
Tray	5 Bill, 8 Coin
Security	Lock & Key
Dimension	410 (W) x 405 (D) x 90 (H) mm
Software driver	ESC/POS, OPOS, JPOS : Windows 10

MSR (OPOS)



Model	MSR (OPOS)
Track Support	3 Tracks (Track 1/2/3)
Interface	USB
Swipe speed	12.7cm to 139.7 cm (5 to 55") per sec, Bi-directional
Head Life	1,000,000 passes Minimum
Color	Black
Software driver	OPOS : Windows 10

Customer display



Model	2x20 Line Customer display	
Characters	20 Characters x 2 Lines	
Display Type	Graphic LCD with Blue backlight	VFD Green display
Brightness	1000cd/m ²	700cd/m ²
Power	DC 5V	
Interface	USB	
Software driver	OPOS / JPOS : Windows 10	

Second display



Model	Second Display Non Touch	
LCD Type	TFT LCD (LED backlight)	
Display	9.7 inch Non Touch	10.1 inch Non Touch
Resolution	1024X768	1200X800
Brightness	300 cd/m ²	
Display Interface	HDMI	USB
Display Input	DC 12V	DC 3.3V
Color	Black	

Essae-Teraoka Pvt. Ltd.

#410, 100ft Road, 4th Block,
Koramangala, Bengaluru-560 034

info@essae.com

<https://www.essae.com>

+91 80 2511 3021

1-800-425-3111

+91 78488 12346



Your Essae representative