

POS-615

POS System

Essae[®]
...for Excellence



Core i3/i5 Processor



PCAP Touch



Windows



M.2 NVMe SSD



Wi-Fi



Powered by the latest Core i3 & i5 Processor. Delivers exceptional performance & power even in the most demanding applications.



Technical Specifications

Model	POS-615C	
CPU	Intel Core i3 1115G4 11th gen 3.00 GHz up to 4.10 GHz Processor 6 MB Cache Memory	Intel Core i5 1235U 12th gen 3.30 GHz up to 4.40 GHz Processor 12 MB Cache Memory
Storage Memory	128 GB M.2 NVMe SSD or 256 GB NVMe SSD	
System Memory	4 GB or 8 DDR4 RAM 1 x SO-DIMM Slot	
Operator Display		
Size	38.1 cm (15") TFT LCD with LED backlight, Anti-glare	
Resolution / Brightness	1024 x 768 / 350 nits	
Touch Screen	Projected Capacitive Touch (PCAP) - True Flat	
External Interface ports		
USB	6	
Serial (DB9)	3	
Network	1 x Gigabit LAN	
Display Port	1 x HDMI (Independent)	
Audio	1 x Line out & Mic in	
Factory options	1 x M.2 Wi-Fi + BT	
Environmental		
Operating Temperature	5°C ~ 40°C	
Power Adapter	DC 12 V / 5 A	
Dimension (W x D x H)	4° tilt angle : 382 mm x 220 mm x 356 mm ; 84° tilt angle : 382 mm x 294 mm x 300 mm	
Optional Accessories		
Printer	Thermal printer, 79.5 + 0.5 mm paper, 220 mm/sec, Auto-cutter 2D Barcode : QR code support, Interface : Serial+USB+LAN	
Cash Drawer	5-Bill/8-Coin metal cash drawer with lock & key and micro switch	
MSR	3 Track-OPOS compliant, USB interface	
Customer display	20 chars x 2 lines customer display 9.7 inch second display non touch	
Mounting Options	VESA-compliant wall mount kit	
Net Weight	6.1 kg (approx)	
Operating System		
Operating System Supports	Windows 10 IoT, Linux (subject to confirmation)	

Front view



Optional accessories



Second display



MSR



2 lines customer display

Essae-Teraoka Pvt. Ltd.

#410, 100ft Road, 4th Block,
Koramangala, Bengaluru-560 034

info@essae.com

https://www.essae.com

+91 80 2511 3021

1-800-425-3111

+91 78488 12346



Your Essae representative